CRUDE GLYCERINE 70%



General Information				
Synonym	1,2,3-propanetriol			
Origin	Argentina	C	Н	
H.S. code	1520.00.00	HO		
CAS number	56-81-5			
Molecular weight	90-100 g/mole			

Application

Refined glycerine	It is used in the production of different grades of refined glycerine.	
Epichlorohydrin	It is used to manufacture epichlorohydrin, which is used to manufacture epoxy resin.	
Propanediol	It is used to manufacture 1,3-propanediol.	
Polyols	Polyols It is used to manufacture polyols, which is used in the production of polyurethane foam.	
Cattle feed It is used as a source of carbohydrates in animal and poultry feed.		

Specification

Property	Units	Value
Appearance at 25°C		Light yellow to dark brown, viscous liquid
Glycerol content	%	70 – 82
Water	% (m/m)	0.5 - 6.0
Methanol	%	2.0 - 4.0
Ash	%	3.0 - 6.0
Viscosity at 20°C	cSt	350 – 550
Density at 20°C	g/ml	1.15 – 1.23
MONG (methanol included)	% (m/m)	8.0 – 16.0

Packaging

• 1 @ 22 MT Flexi Bag, 22 MT / 20' FCL

Tradeasia International Pte Ltd 133 Cecil Street # 12-03 Keck Seng Tower Singapore 069535 Republic Of Singapore Telp : +65 6227 6365 Fax : +65 6225 6286 Email : contact@chemtradeasia.com

