

CRUDE GLYCERINE 80% MIN



General Information

Origin	Argentina
HS Code	1520.00.00
Cas No.	56-81-5
Appearance	Light yellow to dark brown, viscous liquid

Application

Chemical Industry	Crude glycerine can be further processed into a pure form, creating refined glycerine. It is also used to manufacture epichlorohydrin, which is used to manufacture epoxy resin. Crude glycerin can also be used to manufacture 1,3-propanediol.nature.
Oil Industry	It is used to manufacture polyols, which is used as a raw material for the production of polyurethane. Polyurethanes are used to manufacture flexible and rigid foams.
Feed Industry	It is used in the production of animal and poultry feed as a source of carbohydrates. It also has a high absorption rate in animals and rich in energy. Once absorbed by animals, it is converted to glucose by the enzyme glycerol kinase for energy production in the liver of animals.

Specification

Parameter	Specification	Method
Purity (min)	Min 80%	BS 5711-3
Ash	Max 8%	BS 5711-6
Methanol	Max 0,5%	Cromatography
MONG	Max 2,5%	BS 5711-9
Salt (as NaCl)	Max 7%	BS 5711-12
Water (Karl Fisher Method)	Max 14%	BS 5711-8

Packaging

20 MT / Flexi Bag