

CRUDE GLYCERINE 80% MIN



General Information

Origin	Thailand
HS Code	1520.00.00
Cas No.	56-81-5
Appearance	Amber, Clear

Application

Chemical Industry	Crude glycerine can be further processed into a pure form, creating refined glycerine. It is also used to manufacture epichlorohydrin, which is used to manufacture epoxy resin. Crude glycerin can also be used to manufacture 1,3-propanediol.nature.
Oil Industry	It is used to manufacture polyols, which is used as a raw material for the production of polyurethane. Polyurethanes are used to manufacture flexible and rigid foams.
Feed Industry	It is used in the production of animal and poultry feed as a source of carbohydrates. It also has a high absorption rate in animals and rich in energy. Once absorbed by animals, it is converted to glucose by the enzyme glycerol kinase for energy production in the liver of animals.

Specification

Analysis Item	Specification	Reference Method
Appearance	Amber, Clear	-
Glycerol content (%wt)	80 min	BS 5711-3
pH	6-8	pH Meter
Density (g/cm ³)	1.260 max	ASTM D 4052
Methanol (%wt)	5 max	Moisture Balance
Water Content (%wt)	6 max	EN ISO 12937
Salt as NaCl (%wt)	5 max	In-house
Ash Content (%wt)	3 max	BS 5711-6
M.O.N.G (%wt)	Report	Calculation

Packaging

24 MT / Flexi Bag